

Users manual

Features:

full range professional speaker, professional and efficient transducers, computer simulating design.
Two transducers two way full range
High SPL, high sensitivity speaker
One 8" woofer with big power
One 1" compression driver with PEI
diaphragm
Drived by single amplifier
140°×140°wide dispersion can get the
better covering
Computer anolog design bring better
frequency response and phase

■ Two transducers two way phase-reversed

background music, bar, dance hall and other public avenues
 Suitable to be as monitor and sound compensation for any big audio project and touring performance


Flexible and convenient installation modeUsed for full range sound reinforcement,


language reinforcement for meeting system,


Specifications:


Fequency Response(-3dB):	85Hz-19kHz
Sensitivity(1m/1W):	93dB
Crossover Frequency:	2.5kHz
Dispersion(H \times V):	140°×140°
Rated Power(RMS):	150W
Rated Impedance:	8 Ohm
DC Impedance:	5.6 Ohm
THD:	<3%
Input Connectors:	Screw Terminal
Net Weight(1Pc):	8kg
Gross Weight(1Pc):	10kg
Dimensions (W \times D \times H):	258×247×408mm
Packaging Dimensions 1pcs/pack(W \times D \times H):	$320 \times 310 \times 490$ mm

Cabinet Dimension:













Installation drawing:









Users manual

TLA FULL RANGE PROFESSIONAL SPEAKER CS200